




GL408/412e

The Power of Performance



Emulations*



Easy-To-Change Printhead



Large LCD Display Panel



RFID Designed Printer



95011012600000131

Streamlined Features

- Emulations
- RFID Ready
- SATOnet CONNECT™ with Ethernet or Wireless IF
- 3-Port Communication (STD): USB, Parallel, Serial
- Up to 10 ips Print Speed
- Online Barcode Verification

Industry Verticals

- Aerospace
- Automotive
- Distribution
- Manufacturing
- Logistics
- Government
- Health Care
- Transportation

Industry Applications

- Compliance Labeling
- Service Bureaus
- Shipping/Receiving
- Asset Tracking
- WMS
- Logistic Tracking
- Retail Labeling
- Laboratory



General Specifications

The Standard for Reliable
Barcode Printing

GL408/412e

PRINTER MODEL		GL408e	GL412e
PRINT SPECIFICATIONS			
Print Method		Direct Thermal/Thermal Transfer	
Print Resolution		203 dpi (8 dots/mm)	305 dpi (12 dots/mm)
Print Speed		Up to 10 ips (254 mm/sec)	
Max. Print Area		4.09" (104 mm) W x 98.98" (2514 mm) L	
MEDIA SPECIFICATIONS			
Sensor Type		Adjustable Reflective Sensor (for use with pre-printed marks) Adjustable See-Through Sensor (for die-cut labels with gap)	
Media Type		Roll and Fanfold, Paper, Labels, Synthetics	
Media Size	Width	0.87" (22 mm) - 5.04" (128 mm)	
	Length (Continuous)	0.24" (6 mm) - 15.63" (397 mm)	
	Length (Tear-Off)	0.67" (17 mm) - 15.63" (397 mm)	
	Thickness	0.002" - 0.0106" (0.06 mm - 0.268 mm)	
Media Roll Size	Outer Diameter	Max. 10.43" (265 mm)	
	Inner Diameter	1.5" (38.1 mm) to 4" (101.6 mm)	
	Wind Orientation	Face In or Face Out	
Ribbon	Width	Max. 5.04" (128mm)	
	Length	Up to 1476' (450 m)	
	Type	Coated Side In or Out	
FONT / SYMBOLOGIES			
Font		U, S, M, WB, XS, XU, XM, XB, XL, OUTLINE, OCR-A, OCR-B, WL, CG Times, CG Triumvirate	
Barcode Symbologies	Linear	UPC-A/E, UCC/EAN-128, Interleaved 2 of 5, CODE 39, CODE 128, EAN-8/13, CODE 93, RSS-14, POSTNET, NW-7, Matrix 2 of 5, MSI, Bookland	
	2-Dimensional	Data Matrix, PDF417, Macro PDF, Maxicode, Micro PDF417, Composite Symbology, QR Code	
COMMUNICATION INTERFACE			
Interfaces	Standard	IEEE1284 (ECP Compatible), RS232C, USB (2.0)	
	Option	Wireless Ethernet (802.11b/g), LAN (10/100BaseT)	
MEMORY			
Memory		32 MB DRAM, 8 MB Flash ROM, Selectable extended Flash Memory cartridge 32 MB option	
OPERATING CHARACTERISTICS			
Power Requirements		100-120/200-240 Volts AC \pm 10%, 50/60 Hertz \pm 5%	
Environment	Operating	41° - 104°F (5° - 40°C), 15 - 85% RH, non-condensing	
	Storage	-4° - 140°F (-20° - 60°C), 15 - 85% RH, non-condensing	
Dimensions		10.75" W (271 mm) x 18" D (455 mm) x 12" H (305 mm)	
Weight		33 lbs. (15 kg)	
OPTIONS			
Label Cutter, Label Dispenser, External/Internal Rewinder, Real Time Calendar/Clock, Online Barcode Verification, RFID			

*PGL is a trademark of Printronix, Inc. TGL is a trademark of the Toshiba TEC Corporation. The acronyms used to identify the programming languages of non-SATO products may be the property of their respective companies and are used here to identify their various programming languages, used only for explanation without intent to infringe. SATO makes no claims to the authenticity of their command language or functionality. Specifications subject to change without notice.

SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273
Phone: (704) 644-1650 Fax: (704) 644-1662
E-mail: sato-sales@satoamerica.com